JI - 6 Sprinkler





Irrigation
Full Coverage



Pasture Irrigation



Field Crops



Crop Coloring



Dust Suppression



Heap Leaching



Waste Water Reuse

Product Supplied with Hologram which indicate originality & best quality.

Features & Benefits



Jet Breaker Arrangement Uniform distribution profile with adjustable jet breaker arrangement



Interchangeable Nozzles
Various interchangeable
nozzles provide better control
in watering and irrigation of
desired area and crops

Hydrodynamically Designed



Finger-Tip Adjustment
User friendly, Stainless Steel
fingertip adjustment to part
circle mechanism (for part
circle raingun)



Black Cap For Protection of SS Spring

Completely closed Plastic protection cap protects the spring from sand, frost gives longer life to sprinkler



Innovative Swing Arm

Well balanced swing arm ensures smooth and uniform



Equipped with Quality Washers

Special washers used to give uniform & hassle free rotation along with leakage prevention

JI-6

Additional Features

- Full & Part Circle impact sprinkler
- Corrosion proof I-beam construction for added strength
- Easy to install and maintain
- Uniform precipitation rate
- Each batch is tested for stringent quality parameters

Application

 Suitable for field crops like corn, wheat, sugarcane, dust control, waste water spray crops.

Specification

Discharge: 116 to 306 lpmWetted Radius: 17 to 26 m

Operating Pressure: 1.5 to 4.0 Kg/cm²
 Inlet Connection: 1.25" Female Threaded

• Usability: Quick Connect Assembly



Technical Specifications

Full Circle & Part Circle

(Trajectory 30°)

Nozzle (mm)	Spreader Nozzle (Dia) mm	*P	Q	R
		(kg/cm²)	(lpm)	(m)
10	7.0 & 3.1	1.5	116	17.0
		2.0	135	18.0
		4.0	191	23.0
12	7.0 & 3.1	1.5	148	18.0
		2.0	171	19.5
		4.0	245	25.0
14	7.0 & 3.1	2.0	216	20.5
		3.0	265	23.5
		4.0	306	26.0

Note: Sprinklers are tested under standard test conditions.

P= Pressure; Q= Discharge; R = Radius

Ordering Specifications

Code	Description for Standard Nozzle 14 mm	
JI6SD147114F	SPRINKLER LR JI6PC 14X7.0MM FEM	

Note: 10 & 12 mm Nozzle are supplied with standard nozzle as a kit.

JI6SD147114F